

We see what you can't. The future of flame detection is here.

Flame Simulator

FS301

The FS301 is used to test the complete range of FDS flame detectors; intelligent visual flame detectors and radiant flame detectors; without the need for scaffolding.

The FS301 Flame Simulator produces a unique flame pattern recognized by the FDS product line.

The detectors in turn initiate a full alarm function test.



Features and Benefits

Rugged Design

The FS301 is ATEX certified for operation in Zones 1 and 2 hazardous areas. The simulator is supplied with a rugged transit case for safe transportation to locations worldwide.

Long Range Testing

The unit is battery powered and can functionally test our detectors at distances of up to 26 feet. This greatly reduces maintenance costs by removing the need for scaffold or ladder access.

Ease of Maintenance

The simulator is a completely self-contained unit designed for hand held use by a single operator. A single charge of the batteries is sufficient to test in excess of one hundred detectors.

Meets Operator Specification

Some Operators and Certifying Bodies state that a separate test source be used to ensure correct flame detector operation. The FS301 ensures these requirements are met for the complete FDS product family.

Technical Specification

Environmental

Operating Temp: +14°F to +122°F (-10°C to +50°C)
Storage Temp: +14°F to +122°F (-10°C to +50°C)
Humidity: 0 to 95% RH non-condensing

Operating Voltage

4.8 Vdc Nominal; 4 x 1.2 GP180AAH batteries

Power Consumption

35 W (Typical)

Transit Cage

Dimensions: 16L x 180H x 7W (Inches)
Weight: 13.2 lbs (6 Kg)

Sensitivity

Coverage: 1 degree beam divergence
Range: 10 to 26 feet

Enclosure

Dimensions: 4" Diameter x 8 "Length (inches) 100 mm
Dia x 200 mm
Material: Copper free aluminum
Entry size: Fitted Ex db push button switch
Weight: Aluminum 5.5 lbs (2.5 Kg)

Certifications

ATEX  II 2 (2) G Ex db (op is T6 Gb) IIC T6 Gb IP66

